



High-Density, Gigabit Gateways

GXW4200 series

The GXW4200 high-density FXS gateway series enables businesses of all sizes to create a cost-effective hybrid IP and analog telephone system that offers the benefits of VoIP communications and takes advantage of Gigabit speeds while preserving investment on existing analog phones, fax machines and legacy PBX systems. The GXW4200 series includes 16/24/32/48 FXS ports, a Gigabit network port and features broad interoperability with most service providers, soft-switches and SIP-based environments.



A single
10/100/1000Mbps
auto-sensing RJ45
port



TLS and SRTP
security
encryption
technology to
protect calls and
accounts



Automated
provisioning
options include
TR-069 and XML
config files



Supports
3-way voice
conferencing



Failover SIP
server feature
automatically
switches to
secondary server if
main server loses
connection



Supports T.38 Fax
for creating Fax-
over-IP



Supports a wide
range of caller ID
formats



Use with
Grandstream's
UCM series of
IP PBXs for Zero
Configuration
provisioning



Supports advanced telephony features, including
call transfer, call forward, call-waiting, do not
disturb, message waiting indication, multi-
language prompts, flexible dial plan and more

| | |
|--|---|
| Telephone Interfaces | GXW4216/4224/4232: 16/24/32 x RJ11 & 1/1/2 50-pin Telco connectors GXW4248: 2 50-pin Telco connectors |
| Network Interfaces | 1 x 10M/100M/1000Mbps auto-sensing RJ45 port |
| LED indicators | LAN Link, LAN Activity, Connection Per Telephone Port |
| LCD display | Backlit 128x32 graphic LCD display with support for multiple languages |
| Voice-over-Packet Capabilities | Window based carrier grade line echo cancellation, dynamic jitter buffer, modern detection & auto-switch to G.711 |
| Voice Compression | G.711, G.723.1, G.76 (40/32/24/16), G.729 A/B, iLBC |
| Fax over IP | T.38 compliant Group 3 Fax Relay up to 14.4kbps and auto-switch to G.711 for Fax Pass-through, Fax data pump V.17, V.21, V.27ter, V.29 for T.38 fax relay |
| Telephony Feature | Caller ID display or block, call waiting, blind or attended call transfer, call forward, do not disturb, 3-way conference, last call return, paging, message waiting indicator LED (NEON LED) support and stutter tone, auto dial |
| QoS | DiffServ, TOS, 802.1P/Q VLAN tagging |
| Network Protocols | TCP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS, DHCP, NTP, TFTP, TELNET, PPPoE, STUN, LLDP |
| DTMF Method | Flexible DTMF transmission methods including in-audio, RFC2833, and/or SIP INFO |
| Signaling | SIP (RFC 3261) over UDP/TCP/TLS |
| SIP Server Profiles & Accounts Per System | 4 distinct SIP server profiles per system and independent SIP account per telephone port |
| Provisioning | TFTP, HTTP, HTTPS, TR069 |
| Security | SRTP, TLS/SIPS, HTTPS (AES-128 encryption for SRTP, TLS and HTTPS) |
| Management | Syslog, HTTPS, Web browser, voice prompt, TR-069 |
| Universal Power Supply | GXW4232/4224/4216: Output: 12VDC, 5A; Input: 100 ~ 240VAC, 50 ~ 60Hz GXW4248: Output: 24VDC, 6.25A; Input: 100 ~ 240VAC, 50 ~ 60Hz |
| Environmental | Operating: 0 °C ~ 40°C; Storage: -20°C ~ 60°C; Humidity: 10% ~90% (non-condensing) |
| Electrical Protection | Over-voltage and over-current protection (ITU-T Recommendation K.21, Basic Test Level) |
| Physical | Unit dimension: 440mm (L) x 255mm (W) x 44mm (H) (1U) (GXW4248) 440mm (L) x 185mm (W) x 44mm (H) (1U) (GXW4216/4224/4232) Unit Weight: 3.21KG; Package weight: 4.31KG (GXW4248) 2.63KG; 3.68KG (GXW4224) 2.57KG; 3.62KG (GXW4224) 2.39KG; 3.48KG (GXW4216) |
| Mounting | Desktop and rack mount with front brackets |
| LED Indicators | Power, LAN Link/Activity, Hard Drive Activity |
| Short & Long Haul | 2 REN, up to 6000ft on 24 AWG wire |
| Caller ID | Bellcore Type 1&2, ETSI, BT, NTT, and DTMF-based CID |
| Disconnect Methods | Busy Tone, Polarity Reversal/Wink, Loop Current |
| Compliance | FCC: Part 15 (CFR 47) Class B CE: EN55022 Class B, EN55024, EN61000-3-2, EN16000-3-3, EN60950-1, RoHS C-TICK; AS/NZS CISPR 22 Class B, AS/NZS CISPR 24, AN/NZS 60950 ITU-T K.21 (Basic Test Level); UL 60950 (power adapter) |